
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☒ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Pool Master Inc.
Product Name: Poolmaster Patch Kit Dry (DISCONTINUED)



MAILING ADDRESS
P.O. BOX 340308, SACRAMENTO, CA 95834-0308

PHONE & FAX NUMBERS: New Office & Warehouse:
Local (916) 567-9800 770 W. DEL PASO ROAD
Toll Free: (800) 854-1776 SACRAMENTO,
CA 95834-1117
FAX: 916-567-9880

MATERIAL SAFETY DATA SHEET

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information for any other purpose may result in a violation of law or constitute grounds for legal action.

SECTION I

MANUFACTURER'S NAME Poolmaster, Inc.	EMERGENCY TELEPHONE NO. (915) 567-9800
---	---

TRADE NAME AND SYNONYMS

Poolmaster Patch Kit Dry

CHEMICAL NAME AND SYNONYMS

CYCLOHEXANONE Tetrahydrofuran/METHYL ETHYL KETONE

CHEMICAL FAMILY

FURANS/KETONES

FORMULA

$\text{CH}_2\text{CH}_2\text{CH}_2\text{CH}_2\text{O}$ $\text{CH}_3\text{COC}_2\text{H}_5$

SECTION II - HAZARDOUS INGREDIENTS

COMPONENT	%	HAZARD DATA
RESIN BLENDS, NOT CONSIDERED TOXIC		N/A
TETRAHYDROFURAN (200ppm)	68%	
METHYL ETHYL KETONE (200ppm)	6%	
CYCLOHEXANONE (200ppm)	1%	

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	115°F (66°C)	Specific Gravity (H ₂ O=1)	0.89
VAPOR PRESSURE (mm Hg.)	114mmhg	Percent Volatile by Volume (%)	70%
VAPOR DENSITY (AIR=1)	2.5	Evaporation Rate (ETHER=1)	2.3
SOLUBILITY IN WATER	GOOD	Freezing Point	-65°F.

APPEARANCE AND ODOR

Clear Liquid, Thick, with Ether Like Odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	10°F (AP)	FLAMMABLE LIMITS	2.3 - 11.8
EXTINGUISHING MEDIA	Foam CO ₂ Dry Chemical		

SPECIAL FIRE FIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

Peroxides are explosive

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	200 ppm, 590 mg/m ³ (ACGIH)
TOXICITY	

SECTION V - HEALTH HAZARD DATA (cont.)**EFFECTS OF OVER EXPOSURE**

Nausea; dizziness; headache, irritates eyes, skin, respiratory tract,
Can cause skin burns.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with flowing water at least 15 minutes
Remove victim to fresh air, and wash affected areas thoroughly,
Consult a physician. Aid breathing if necessary, Never give fluids or
induce vomiting if patient is unconscious or having convulsions.

SECTION VI - REACTIVITY DATA

STABILITY:	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Exposure to light

INCOMPATIBILITY

Lithium aluminum hydride, alkaline earth hydroxides.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon dioxide & carbon monoxide (thermal decomposition)

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	XXX	

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:
Absorb with paper, evaporate, then burn paper.

WASTE DISPOSAL METHOD

Dissolve in benzene, pet ether, or higher alcohol and burn the
solution in properly designed incinerator. Consult State & Local Laws.

SECTION VIII - SPECIAL PROTECTION INFORMATION**RESPIRATORY PROTECTION**

Self-contained breathing apparatus

VENTILATION	LOCAL EXHAUST	Preferred	SPECIAL
	MECHANICAL	If sufficient to maintain TLV	OTHER

PROTECTIVE GLOVES	Gloves	EYE PROTECTION	Goggles
-------------------	--------	----------------	---------

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep container closed and store in cool, dry place. Keep away from
heat, sparks, & open flame.

OTHER PRECAUTIONS

PRECAUTIONARY LABELING: DANGER: Extremely flammable; Liquid &
vapor harmful
Avoid contact with skin, eyes, clothing

The information supplied above is presented in good faith and has been derived from sources believed to be reliable. However, no warranty, express or implied is extended regarding its accuracy or the results to be obtained from its use. Since conditions of use are beyond our control all risks are assumed by the user.